



K型热电偶分度表 K 参考端温度：0℃ 整 10 度 m v 值

℃	0	10	20	30	40	50	60	70	80	90
0	0.000	0.397	0.798	01.203	01.611	02.022	02.436	02.850	03.266	03.681
100	04.095	04.508	04.919	05.327	05.733	06.137	06.539	06.939	07.338	07.737
200	08.137	08.537	08.938	09.341	09.745	10.151	10.560	10.969	11.381	11.793
300	12.207	12.623	13.039	13.456	13.874	14.292	14.712	15.132	15.552	15.974
400	16.395	16.818	17.241	17.664	18.088	18.513	18.938	19.363	19.788	20.214
500	20.640	21.066	21.493	21.919	22.346	22.772	23.198	23.624	24.050	24.476
600	24.902	25.327	25.751	26.176	26.599	27.022	27.445	27.867	28.288	28.709
700	29.128	29.547	29.965	30.383	30.799	31.214	31.629	32.042	32.455	32.866
800	33.277	33.686	34.095	34.502	34.909	35.314	35.718	36.121	36.524	36.925
900	37.325	37.724	38.122	38.519	38.915	39.310	39.703	40.096	40.488	40.879
1000	41.269	41.657	42.045	42.432	42.817	43.202	43.585	43.968	44.349	44.729
1100	45.108	45.486	45.863	46.238	46.612	46.985	47.356	47.726	48.095	48.462
1200	48.828	49.192	49.555	49.916	50.276	50.633	50.990	51.344	51.697	52.049
1300	52.398	53.093	53.093	53.439	53.782	54.125	54.466	54.807		

N型热电偶分度表 N 参考端温度：0℃ 整 10 度 m v 值

℃	0	10	20	30	40	50	60	70	80	90
0	0.000	0.261	0.525	0.793	01.065	01.340	01.619	01.902	02.189	02.480
100	02.774	03.072	03.374	03.680	03.989	04.302	04.618	04.937	05.259	05.585
200	05.913	06.245	06.579	06.916	07.255	07.597	07.941	08.288	08.637	08.988
300	09.341	09.696	10.054	10.413	10.774	11.136	11.501	11.867	12.234	12.603
400	12.974	13.346	13.719	14.094	14.469	14.846	15.225	15.604	15.984	16.336
500	16.748	17.131	17.515	17.900	18.286	18.672	19.059	19.447	19.835	20.224
600	20.613	21.003	21.393	21.784	22.175	22.566	22.958	23.350	23.742	24.134
700	24.527	24.919	25.312	25.705	26.098	26.491	26.883	27.276	27.669	28.062
800	28.455	28.847	29.239	29.632	30.024	30.416	30.807	31.199	31.590	31.981
900	32.371	32.761	33.151	33.541	33.930	34.319	34.707	35.095	35.482	35.869
1000	36.256	36.641	37.027	37.411	37.795	38.179	38.562	38.944	39.326	39.706
1100	40.087	40.466	40.845	41.223	41.600	41.976	42.352	42.727	43.101	43.474
1200	43.846	44.218	44.588	44.958	45.326	45.694	46.060	46.425	46.789	47.152
1300	47.513									



E 型热电偶分度表 E 参考端温度: 0°C 整 10 度 mV 值

°C	0	10	20	30	40	50	60	70	80	90
0	0.000	0.591	01.192	01.801	02.419	03.047	03.683	04.329	04.983	05.646
100	06.317	06.996	07.683	08.377	09.078	09.787	10.501	11.222	11.949	12.681
200	13.419	14.161	14.909	15.661	16.417	17.178	17.942	18.710	19.481	20.256
300	21.033	21.814	22.597	23.383	24.171	24.961	25.754	26.549	27.345	28.143
400	28.943	29.744	30.546	31.350	32.155	32.960	33.767	34.574	35.382	36.190
500	36.999	37.808	39.426	40.236	41.045	41.853	42.662	43.470	44.278	45.085
600	45.085	45.891	46.697	47.502	48.306	49.109	49.911	50.713	51.513	52.312
700	53.110	53.907	54.703	55.498	56.291	57.083	57.873	58.663	59.451	60.237
800	61.022	61.806	62.588	63.368	64.147	64.924	65.700	66.473	67.245	68.015
900	68.783	69.549	70.313	71.075	71.835	72.593	73.350	74.104	74.857	75.608
1000	76.358									

J 型热电偶分度表 J 参考端温度: 0°C 整 10 度 mV 值

°C	0	10	20	30	40	50	60	70	80	90
0	0.000	0.507	01.019	01.536	02.058	02.585	03.115	03.649	04.186	04.725
100	05.268	05.812	06.359	06.907	07.457	08.008	08.560	09.113	09.667	10.222
200	10.777	11.332	11.887	12.442	12.998	13.553	14.108	14.663	15.217	15.771
300	16.325	16.879	17.432	17.984	18.537	19.089	19.640	20.192	20.743	21.295
400	21.846	22.397	22.949	23.501	24.054	24.607	25.161	25.716	26.272	26.829
500	27.388	27.949	28.511	29.075	29.642	30.210	30.782	31.356	31.933	32.513
600	33.096	33.683	34.273	34.867	35.464	36.066	36.671	37.280	37.893	38.510
700	39.130	39.754	40.382	41.013	41.647	42.283	42.922	43.563	44.207	44.852
800	45.498	46.144	46.790	47.434	48.076	48.716	49.354	49.989	50.621	51.249
900	51.875	52.496	53.115	53.729	54.321	54.948	55.553	56.155	56.753	57.349
1000	57.942	58.533	59.121	59.708	60.293	60.876	61.459	62.039	62.619	63.199
1100	63.777	64.355	64.933	65.510	66.087	66.664	67.240	67.815	68.390	68.964
1200	69.536									

T 型热电偶分度表 T 参考端温度: 0°C 整 10 度 mV 值

°C	0	10	20	30	40	50	60	70	80	90
0	0.000	0.391	0.789	01.196	01.611	02.035	02.467	02.908	03.357	03.813
100	04.277	04.749	05.227	05.712	06.204	06.702	07.207	07.718	08.235	08.757
200	09.286	09.820	10.360	10.905	11.456	12.011	12.572	13.137	13.707	14.281
300	14.860	15.443	16.030	16.621	17.217	17.816				



S型热电偶分度表 S 参考端温度: 0℃ 整 10度 mV 值

℃	0	10	20	30	40	50	60	70	80	90
0	0.000	0.055	0.113	0.173	0.235	0.299	0.365	0.432	0.502	0.573
100	0.645	0.719	0.795	0.872	0.950	01.029	01.109	01.190	01.273	01.356
200	01.440	01.525	01.611	01.698	01.785	01.873	01.962	02.051	02.141	02.232
300	02.323	02.414	02.506	02.599	02.692	02.786	02.880	02.974	03.069	03.164
400	03.260	03.356	03.452	03.549	03.645	03.743	03.840	03.938	04.036	04.135
500	04.234	04.333	04.432	04.532	04.632	04.732	04.832	04.933	05.034	05.136
600	05.237	05.339	05.442	05.544	05.648	05.751	05.855	05.960	06.064	06.169
700	06.274	06.380	06.486	06.592	06.699	06.805	06.913	07.020	07.128	07.236
800	07.345	07.454	07.563	07.672	07.782	07.892	08.003	08.114	08.225	08.336
900	08.448	08.560	08.673	08.786	08.899	09.012	09.126	09.240	09.355	09.470
1000	09.585	09.700	09.816	09.932	10.048	10.165	10.282	10.400	10.517	10.635
1100	10.754	10.872	10.991	11.110	11.229	11.348	11.467	11.587	11.707	11.827
1200	11.947	12.067	12.188	12.308	12.429	12.550	12.671	12.792	12.913	13.034
1300	13.155	13.276	13.397	13.519	13.640	13.761	13.883	14.004	14.125	14.247
1400	14.368	14.489	14.610	14.731	14.852	14.973	15.094	15.215	15.336	15.456
1500	15.576	15.697	15.817	15.937	16.057	16.176	16.296	16.415	16.534	16.653
1600	16.771	16.890	17.008	17.125	17.245	17.360	17.477	17.594	17.711	17.826

R型热电偶分度表 R 参考端温度: 0℃ 整 10度 mV 值

℃	0	10	20	30	40	50	60	70	80	90
0	0.000	0.054	0.111	0.171	0.232	0.296	0.363	0.431	0.501	0.573
100	0.647	0.723	0.800	0.879	0.959	01.041	01.124	01.208	01.294	01.381
200	01.469	01.558	01.648	01.739	01.831	01.923	02.017	02.112	02.207	02.304
300	02.401	02.498	02.597	02.696	02.796	02.896	02.997	03.099	03.201	03.304
400	03.408	03.512	03.616	03.721	03.827	03.933	04.040	04.147	04.255	04.363
500	04.471	04.580	04.690	04.800	04.910	05.021	05.133	05.245	05.357	05.470
600	05.583	05.697	05.812	05.926	06.041	06.157	06.273	06.397	06.507	06.625
700	06.743	06.861	06.980	07.100	07.220	07.340	07.461	07.583	07.705	07.827
800	07.950	08.073	08.197	08.321	08.446	08.571	08.697	08.823	08.950	09.077
900	09.205	09.333	09.461	09.590	09.720	09.850	09.980	10.111	10.242	10.374
1000	10.506	10.638	10.771	10.905	11.039	11.173	11.307	11.442	11.578	11.714
1100	11.850	11.986	12.123	12.260	12.397	12.535	12.673	12.812	12.950	13.089
1200	13.228	13.367	13.507	13.646	13.786	13.926	14.066	14.207	14.347	14.488
1300	14.629	14.770	14.911	15.052	15.193	15.334	15.475	15.616	15.758	15.899
1400	16.040	16.181	16.323	16.464	16.605	16.746	16.887	17.028	17.169	17.310
1500	17.451	17.591	17.732	17.872	18.012	18.152	18.292	18.431	18.571	18.710
1600	18.849	18.988	19.126	19.264	19.402	19.540	19.677	19.814	19.951	20.087
1700	20.222	20.356	20.488	20.620	20.749	20.877	21.003			



B型热电偶分度表 B 参考端温度：0℃ 整 10 度 mV 值

℃	0	10	20	30	40	50	60	70	80	90
0	0.000	-0.002	-0.003	-0.002	0.000	0.002	0.006	0.011	0.017	0.025
100	0.033	0.043	0.053	0.065	0.078	0.092	0.107	0.123	0.140	0.159
200	0.178	0.199	0.220	0.243	0.266	0.291	0.317	0.344	0.372	0.401
300	0.431	0.462	0.494	0.529	0.561	0.596	0.632	0.669	0.707	0.746
400	0.786	0.827	0.870	0.913	0.957	1.002	1.048	1.095	1.143	1.192
500	01.241	01.292	01.344	01.397	01.450	01.505	01.560	01.617	01.674	01.732
600	01.791	01.851	01.912	01.974	02.036	02.100	02.164	02.230	02.296	02.363
700	02.430	02.499	02.569	02.639	02.710	02.782	02.855	02.928	03.003	03.078
800	03.154	03.231	03.308	03.387	03.466	03.546	03.626	03.708	03.790	03.873
900	03.957	04.041	04.126	04.212	04.298	04.386	04.474	04.562	04.652	04.742
1000	04.833	04.924	05.016	05.109	05.202	05.297	05.391	05.487	05.583	05.680
1100	05.777	05.875	05.973	06.073	06.172	06.273	06.374	06.475	06.577	06.680
1200	06.783	06.887	06.991	07.096	07.202	07.308	07.414	07.521	07.628	07.736
1300	07.845	07.953	08.063	08.172	08.283	08.393	08.504	08.616	08.727	08.839
1400	08.952	09.065	09.178	09.291	09.405	09.519	09.634	09.748	09.863	09.979
1500	10.094	10.210	10.325	10.441	10.558	10.674	10.790	10.907	11.024	11.141
1600	11.257	11.374	11.491	11.608	10.725	11.842	11.959	12.076	12.193	12.310
1700	12.436	12.543	12.659	12.776	12.892	13.008	13.124	13.239	13.354	13.470
1800	13.585	13.699	13.814							



钨铼 5-钨铼 26 热电偶分度表 W5/26 参考端温度: 0°C 整 10 度 mV 值

°C	0	10	20	30	40	50	60	70	80	90
0	0.000	0.135	0.723	0.412	0.554	0.699	0.845	0.994	01.144	01.451
100	01.451	01.607	01.766	01.925	02.087	02.250	02.415	02.581	02.749	02.919
200	03.089	03.261	03.435	03.609	03.785	03.962	04.141	04.320	04.500	04.682
300	04.864	05.047	05.231	05.416	05.602	05.788	05.976	06.164	06.352	06.541
400	06.731	06.922	07.113	07.304	07.496	07.688	07.881	08.074	08.268	08.461
500	08.655	08.850	09.044	09.239	09.434	09.629	09.824	10.020	10.215	10.411
600	10.606	10.802	10.997	11.193	11.388	11.584	11.779	11.974	12.169	12.364
700	12.559	12.753	12.948	13.142	13.336	13.530	13.723	14.916	14.109	14.302
800	14.494	14.686	14.878	15.069	15.260	15.451	15.641	15.831	16.020	16.209
900	16.397	16.585	16.773	16.960	17.147	17.333	17.519	17.704	17.889	18.074
1000	18.257	18.441	18.623	18.806	18.987	19.169	19.349	19.529	19.709	19.888
1100	20.066	20.244	20.422	20.598	20.775	20.950	21.125	21.300	21.474	21.647
1200	21.820	21.992	22.163	22.334	22.505	22.674	22.844	23.012	23.180	23.347
1300	23.514	23.680	23.846	24.011	24.175	24.339	24.502	24.665	24.827	24.988
1400	25.149	25.309	25.468	25.627	25.785	25.943	26.100	26.257	26.413	26.568
1500	26.723	26.877	27.030	27.183	27.335	27.487	27.638	27.788	27.938	28.087
1600	28.236	28.384	28.531	28.678	28.824	28.970	29.115	29.259	29.403	29.546
1700	29.688	29.830	29.971	30.112	30.252	30.391	30.530	30.668	30.806	30.943
1800	31.079	31.214	31.349	31.483	31.617	31.750	31.882	32.014	32.145	32.275
1900	32.404	32.533	32.661	32.789	32.915	33.041	33.167	33.291	33.415	33.538
2000	33.660	33.782	33.903	34.023	34.142	34.260	34.378	34.495	34.611	34.726
2100	34.840	34.953	35.066	35.177	35.288	35.398	35.506	35.614	35.721	35.827
2200	35.932	36.036	36.139	36.241	36.341	36.441	36.540	36.637	36.733	36.829
2300	36.923	37.015								



钨铼 3-钨铼 25 热电偶分度表 W3/25 参考端温度: 0°C 整 10 度 mV 值

°C	0	10	20	30	40	50	60	70	80	90
0	0.000	0.098	0.199	0.305	0.415	0.528	0.644	0.765	0.888	01.015
100	01.145	01.273	01.414	01.554	01.696	01.840	01.988	02.137	02.290	02.445
200	02.602	02.761	02.923	03.087	03.253	03.420	03.590	03.761	03.935	04.110
300	04.286	04.464	04.644	04.825	05.008	05.192	05.377	05.563	05.751	05.940
400	06.129	06.320	06.512	06.705	06.898	07.093	07.288	07.484	07.681	07.879
500	08.077	08.275	08.475	08.675	08.875	09.076	09.277	09.479	09.681	09.883
600	10.086	10.289	10.492	10.695	10.899	11.103	11.307	11.511	11.715	11.920
700	12.124	12.329	12.534	12.738	12.943	13.147	13.352	13.557	13.761	13.966
800	14.171	14.376	14.580	14.785	14.989	15.194	15.398	15.601	15.805	16.008
900	16.211	16.414	16.617	16.819	17.021	17.223	17.424	17.625	17.826	18.026
1000	18.226	18.426	18.625	18.824	19.023	19.221	19.419	19.616	19.813	20.009
1100	20.206	20.401	20.597	20.791	20.986	21.180	21.373	21.566	21.759	21.951
1200	22.143	22.334	22.525	22.715	22.905	23.094	23.283	23.471	23.659	23.846
1300	24.033	24.220	24.406	24.591	24.776	24.961	25.145	25.328	25.511	25.693
1400	25.875	26.057	26.238	26.418	26.598	26.777	26.956	27.134	27.312	27.489
1500	27.666	27.842	28.018	28.193	28.368	28.542	28.715	28.888	29.061	29.233
1600	29.404	29.575	29.745	29.914	30.083	30.252	30.419	30.587	30.753	30.919
1700	31.085	31.249	31.413	31.577	31.740	31.902	32.063	32.224	32.384	32.543
1800	32.702	32.860	33.017	33.174	33.330	33.485	33.639	33.792	33.945	34.097
1900	34.248	34.398	34.547	34.695	34.843	34.989	35.135	35.279	35.423	35.566
2000	35.707	35.848	35.987	36.126	36.263	36.399	36.535	36.668	36.801	36.933
2100	37.063	37.192	37.319	37.446	37.571	37.694	37.816	37.937	38.056	38.174
2200	38.290	38.404	38.517	38.628	38.738	38.845	38.951	39.055	39.158	39.258
2300	39.256	39.453								